

Wall Mount – Economy Series Reverse Osmosis System



w/cover

STANDARD FEATURES

- RO Elements: Extra Low Energy Thin Film
- Pressure Vessels: 304 Stainless Steel (SS)
- Frame: 409 SS
- Pump: Vane type
- Pump Pressure Gauge (liquid filled)
- Low Pressure Cutoff Switch
- Pre Filter: 1 Micron Sediment
- Inlet Filter Gauge
- Inlet Feed Electric Solenoid Valve
- Inlet Manual Shutoff Valve
- Product Reverse Flow Check Valve
- Waste Recycle Valve

DIMENSIONS

Height: 50 inches

Depth: 7 inches

Width: 24 inches

SPECIFICATIONS

| Elements | Production* | Recovery | Motor** | Weight (Approx.) | Inlet*** | Outlets |
|-----------------|-------------|----------|---------|------------------|-----------|---------|
| Qty. 1 (4") | 1,500 GPD | 50% | 1/2 HP | 120 Lbs. | 1/2" FNPT | 3/8" JG |
| Qty. 1 (2 1/2") | 750 GPD | 50% | 1/2 HP | 110 Lbs. | 1/2" FNPT | 3/8" JG |

* Approximate product flow based on properly pretreated feed water of 1000 ppm TDS (as NaCl), 15° C (59° F) and silt density index less than 3. Production capacity may vary due to feed water temperature, pressure, quality and product back pressure.

** Electrical: Standard 120 VAC 60 HZ Single Phase

*** Inlet Pressure: 20 PSI Minimum (when running), 80 PSI Maximum.

Premier Water Solutions Ltd

Head Office: No. D, Shreeji Road Off North Airport Rd., Nairobi

P. O. Box 38560-00623, Nairobi, Kenya Tel: (+254) 20 2369654, 0724-238955

Email: info@premierwater.co.ke Web: www.premierwater.co.ke

We reserve the right to amend these specifications at any time without notice. The only warranty is the standard written Premier Water Solutions Ltd warranty. We make no other warranty, expressed or implied. Consult factory for details.